

## C-3- High temperature Crepe Paper Tape

**Description:** Davik C-3, high temperature resistance Masking Tape is made of high-grade white masked paper and coated on one side with acrylic pressure sensitive adhesive.

**Features:** Excellent thermal stability, easy handling, smooth crepe backing, exhibit very good strength.

**Application:** Ideal for mid-range temperature applications. Commonly used as masking material in operating conditions where higher temperature resistance is required, such as the thermal curing for drying fresh automotive paint.

### Typical Properties

<i>Properties</i>	<i>Unit</i>	<i>Values</i>	<i>Test Method</i>
<i>Total Weight</i>	<i>(g/m<sup>2</sup>)</i>	<i>106±8</i>	<i>ASTM-D1000</i>
<i>Base Weight</i>	<i>(g/m<sup>2</sup>)</i>	<i>50</i>	<i>ASTM-D1000</i>
<i>Adhesive</i>	<i>-</i>	<i>Rubber</i>	
<i>Tensile Strength MD</i>	<i>(N/in)</i>	<i>≤75</i>	<i>ASTM-D1000</i>
<i>Elongation</i>	<i>(%)</i>	<i>≤5</i>	<i>ASTM-D1000</i>
<i>Adhesion to Steel</i>	<i>(N/in)</i>	<i>≤6.5</i>	<i>ASTM-D1000</i>
<i>Tack</i>	<i>(#14/cm)</i>	<i>≥20</i>	<i>PSTC-6</i>
<i>Holding Power</i>	<i>(min)</i>	<i>≤1000</i>	<i>PSTC-7</i>
<i>Service Temperature</i>	<i>(°C)</i>	<i>(+)120</i>	<i>Internal Method</i>
<i>Width</i>	<i>(mm)</i>	<i>25,50,75,100</i>	
<i>Length</i>	<i>(mm)</i>	<i>50 m</i>	
<i>Core</i>	<i>(mm)</i>	<i>76 (3')</i>	
<i>Color</i>		<i>Beige</i>	

The above information is for reference only and should not be employed as inspection standard.

***Storage and Shelf Life:***

*6 month from manufacture day, when stored at 15-30°C (59 - 86°F), 50% relative humidity out of direct sunlight.*

***Surface Preparation before application:***

*The surface to which the tape is applied should be clean, dry, and free of grease and oil.*

***Warranty:***

*Data presented is the average results of analysis made on our standards production.*

*We recommend each user determine the suitability of the products for the intended use.*