

## FL7915- Finger Lift

**Description :** Self-adhesive tape consists of Polypropylene carrier coated with high grade pressure sensitive Acrylic water based adhesive, includes none adhesive zone for an easy peeling and reclosing a package.

**Features :** Solvent free  
Printing technology up to 2 colors  
UV-resistant  
Excellent ageing.  
High clarity.

**Application :** Excellent performance tape for an easy-to-use resealable closure of a package.

### Typical Properties

Properties	Unit	Values		Test Method
Thickness <i>film</i> <i>total ± 5%</i>	Micron (Mil)	35 (1.41)	50 (2.0)	PSTC- 133
		55(2.16)	70 (2.7)	
Tensile strength	N/mm <sup>2</sup>	150	150	ASTM D-882
Elongation	%	210	210	ASTM D-882
Adhesion to steel	N/inch	8.5 ± 2	8.5 ± 2	PSTC-101
Colors	Transparent			---
Widths*	mm	30, 42		---
Lengths*	M	500, 850		---
Core	mm (in)	76 (3)		---

\* other sizes upon request

#### **Storage and Shelf Life:**

One year when stored at 15-30°C (59-86°F). 50% relative humidity. Out of direct sunlight.

#### **Surface Preparation before application:**

The surface to which the tape is applied should be clean, dry, and free of grease and oil.

#### **Warranty:**

Data presented is the average results of analysis made on our standards production.

We recommend each user determine the suitability of the products for the intended use.