

StrapPack

Semi-Automatic Strapping Machine

Introducing iQ-400, Strapack's new semi-automatic strapping machine with dual tension mode. This allows for a wide variety of applications with just a flick of a switch.



iQ-400

- The iQ-400 is a durable and heavy-duty strapping machine designed to withstand various harsh environments.
- The iQ-400 is yet amazingly quiet to operate and well suited for office use also.
- The iQ-400 has less moving parts, which makes it easy to maintain and keeps the operation cost low.
- All electric parts are arranged in one side of the machine, enclosed in the cabinet, for easy maintenance and protection of crucial parts.
- The iQ-400 runs strap from 5 to 15.5 millimeters without additional parts.
- The torque tension mode is suitable for stronger tension or to strap compressible packages, while the stroke tension mode is best for soft tension or quick operation.
- Tool-free access to frequently accessed areas for easy maintenance.
- Hinged tables are easy to remove for daily maintenance.
- Adjustable legs are available upon request. With this option, table height can be adjusted from 775.5 up to 925.5mm.
- To make the machine more robust, side and rear panels between the legs are available upon request.

Standard Specifications

| | | | |
|--------------------------------|---------------|--|--|
| Dimensions | Width | 780mm | 30-11/16in. |
| | Height | 777mm (incl. work guide) | 30-9/16in. (incl. work guide) |
| | Depth | 540mm | 22-7/16in. |
| | Weight | 46kg | 101lbs. |
| Table Height | | 752mm | 29-5/8in. |
| Min. Package Size | | W 100mm x H 30mm | W 3-7/8in. x H 1-1/8in. |
| Joint / Strap / Coil | | heat seal / polypropylene ID 200 or 230mm x W 200mm | heat seal / polypropylene ID 8 or 9in. x 8in. |
| Strap Width / Thickness | | 5, 6, 9, 12, 15.5mm / 0.45-0.7mm | 1/4, 3/8, 1/2, 5/8in. / 0.017-0.027in. |
| Strap Tension | | Max. 449N (45,8kgf) | Max. 100,9lbf |
| Power Supply | | 220-240V Single phase | 50/60Hz 0.40kVA |

Dimensions and specifications are subject to change without notice.

Modification rights reserved.

© 2018 Strapack

DISTRIBUTED BY:

ISO 9001 and 14001 Certified



STRAPACK CORPORATION

8-16-6, Ginza, 104-0061 Chuo-ku, Tokyo, JAPAN
Phone: +81 3 6278 1806 Fax: +81 3 6278 1807
(URL) <http://www.strapack.com> (e-mail) info@strapack.com

STRAPACK INC.

33508, Central Avenue, Union City, CA 94587-2097, U.S.A.
Phone: +1 510 475 6000 Fax: +1 510 475 6090
(e-mail) hayward1@strapack.com

STRAPACK N.V./S.A.

Uilenbaan 200, 2160 Wommelgem, BELGIUM
Phone: +32 3 355 15 20 Fax: +32 3 355 15 21
(e-mail) europe@strapack.be